

Perl Package Distribution

Perl Package Distribution

Published Wed Nov 12 11:25:56 2003

Table of Contents

I. Prolog	5
SOFTPKG	6
II. Elements	7
ABSTRACT	8
AUTHOR	9
CODEBASE	10
DEPENDENCY	11
IMPLEMENTATION	12
INSTALL	13
LANGUAGE	14
LICENSE	15
OS	16
OSVERSION	17
PERLCORE	18
PROCESSOR	19
SOFTPKG	20
TITLE	21
UNINSTALL	22
III. Examples	23
Example sample.ppd	24

Prolog

Name

SOFTPKG -- --

SOFTPKG

Synopsis

<i>Name</i>	<i>System</i>	
SOFTPKG	ppd.dtd	

Description

The DTD for PPD documents is available from the ActiveState website and the latest version can be found at <http://www.ActiveState.com/PPM/DTD/ppd.dtd>

Elements

Element tree

- SOFTEPKG
 - IMPLEMENTATION
 - INSTALL
 - CODEBASE
 - OSVERSION
 - LANGUAGE
 - UNINSTALL
 - DEPENDENCY
 - OS
 - PROCESSOR
 - PERLCORE
 - LICENSE
 - ABSTRACT
 - TITLE
 - AUTHOR

Name

ABSTRACT -- --

ABSTRACT

Synopsis

<i>Mixed Content Model</i>
ABSTRACT ::= (#PCDATA)
<i>Attributes</i>
<i>None</i>

Description

Used to provide a short description outlining the nature and purpose of the Perl Package. Only one instance should be present.

Parents

These elements contain ABSTRACT: SOFTRPG.

Name

AUTHOR -- --

AUTHOR

Synopsis

<i>Mixed Content Model</i>
<pre>AUTHOR ::= (#PCDATA)</pre>
<i>Attributes</i>
<i>None</i>

Description

Used to provide information about the author(s) of the Perl Package. Multiple instances are valid.

Parents

These elements contain AUTHOR: SOFTEPKG.

Name

CODEBASE -- --

CODEBASE

Synopsis

<i>Content Model</i>		
CODEBASE ::= EMPTY		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
FILENAME	CDATA	#IMPLIED
HREF	CDATA	#REQUIRED

Description

Indicating a location where an archive of the Perl Package can be retrieved. Multiple instances are valid, and can be used to indicate multiple possible locations where the same version of the Perl Package can be retrieved.

FILENAME

???

HREF

A reference to the location of the Perl Package distribution.

Parents

These elements contain CODEBASE: IMPLEMENTATION.

Name

DEPENDENCY ---

DEPENDENCY

Synopsis

<i>Content Model</i>		
DEPENDENCY ::= EMPTY		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
VERSION	CDATA	#IMPLIED
NAME	CDATA	#REQUIRED

Description

Used to indicate a dependency this Perl Package has on another Perl Package. Multiple instances are valid.

VERSION

Version number of the dependency, in comma-delimited format (e.g. ``1,0,0,0").

NAME

Name of the package that this implementation is dependant upon.

Parents

These elements contain DEPENDENCY: IMPLEMENTATION.

Name

IMPLEMENTATION -- -- describe a particular implementation of the Perl Package

IMPLEMENTATION

Synopsis

<i>Element Content Model</i>
IMPLEMENTATION ::=
(CODEBASE DEPENDENCY LANGUAGE OS OSVERSION PERLCORE
PROCESSOR INSTALL UNINSTALL) *
<i>Attributes</i>
<i>None</i>

Description

Used to describe a particular implementation of the Perl Package. Multiple instances are valid, and should be used to describe different implementations/ports for different operating systems or architectures.

Parents

These elements contain IMPLEMENTATION: SOFTPKG.

Children

The following elements occur in IMPLEMENTATION: CODEBASE, DEPENDENCY, INSTALL, LANGUAGE, OS, OSVERSION, PERLCORE, PROCESSOR, UNINSTALL.

Name

INSTALL -- -- provide either a reference to an installation script

INSTALL

Synopsis

<i>Mixed Content Model</i>		
<pre>INSTALL ::= (#PCDATA)</pre>		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
HREF	CDATA	#IMPLIED
EXEC	CDATA	#IMPLIED

Description

Used to provide either a reference to an installation script or a series of commands which can be used to install the Perl Package once it has been retrieved. If the EXEC attribute is not specified, the value is assumed to be one or more commands, separated by `;'. Each such command will be executed by the Perl `system()'function. Only one instance should be present.

HREF

Reference to an external script which should be retrieved and run as part of the installation process. Both filenames and URLs should be considered valid.

EXEC

Name of interpreter/shell used to execute the installation script. If the value of EXEC is `PPM_PERL', the copy of Perl that is executing PPM itself (\$^X) is used to execute the install script.

Parents

These elements contain INSTALL: IMPLEMENTATION.

Name

LANGUAGE -- --

LANGUAGE

Synopsis

<i>Content Model</i>		
LANGUAGE ::= EMPTY		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
VALUE	CDATA	#REQUIRED

Description

Used to specify the language used within the given implementation of the Perl Package. Only one instance should be present.

VALUE

Parents

These elements contain LANGUAGE: IMPLEMENTATION.

Name

LICENSE -- --

LICENSE

Synopsis

<i>Content Model</i>		
LICENSE ::= EMPTY		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
HREF	CDATA	#REQUIRED

Description

Indicating the location of the appropriate license agreement or copyright notice for the Perl Package. Only one instance should be present.

HREF

Required attribute. A reference to the location of the license agreement or copyright notice for this package.

Parents

These elements contain LICENSE: SOFTRPKG.

Name

OS --- the operating system required for this implementation

OS

Synopsis

<i>Content Model</i>		
OS ::= EMPTY		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
VALUE	CDATA	#REQUIRED

Description

Used to outline the operating system required for this implementation of the Perl Package. Multiple instances are valid. Valid values can be taken from the OSD Specification and it's OS element.

VALUE

The name of the operating system required for this implementation of the Perl Package. This value should be obtained from Config.pm as 'osname'.

Parents

These elements contain OS: IMPLEMENTATION.

Name

OSVERSION -- -- the required version of the operating system

OSVERSION

Synopsis

<i>Content Model</i>		
OSVERSION ::= EMPTY		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
VALUE	CDATA	#REQUIRED

Description

Used to outline the required version of the operating system required for this implementation of the Perl Package. Only one instance should be present.

VALUE

The version of the operating system required for installation of this implementation of the package, in a comma-delimited format (e.g. ``3,1,0,0").

Parents

These elements contain OSVERSION: IMPLEMENTATION.

Name

PERLCORE -- -- the minimum version of the Perl core distribution

PERLCORE

Synopsis

<i>Content Model</i>		
PERLCORE ::= EMPTY		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
VERSION	CDATA	#REQUIRED

Description

Used to specify the minimum version of the Perl core distribution that this Perl Package is to be used with. Only one instance should be present.

VERSION

Version of the Perl core that is required for this implementation of the Perl Package.

Parents

These elements contain PERLCORE: IMPLEMENTATION.

Name

PROCESSOR -- --

PROCESSOR

Synopsis

<i>Content Model</i>		
PROCESSOR ::= EMPTY		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
VALUE	CDATA	#REQUIRED

Description

Outlining the cpu required for this implementation of the Perl Package. Only one instance should be present.

VALUE

CPU required for the installation of this implementation of the Perl Package. The following values are all valid according to the OSD Specification: x86 alpha mips sparc 680x0

Parents

These elements contain PROCESSOR: IMPLEMENTATION.

Name

SOFTPKG -- -- root element of a description of a software package

SOFTPKG

Synopsis

<i>Element Content Model</i>		
SOFTPKG ::= (ABSTRACT AUTHOR IMPLEMENTATION LICENSE TITLE) *		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
NAME	CDATA	#REQUIRED
VERSION	CDATA	#IMPLIED

Description

It's the root element of a description of a software package, in Perl Package Distribution (PPD) format which is an XML application.

HISTORY : v0.1 - Initial release

SEE ALSO : OSD Specification <http://www.microsoft.com/standards/osd/>

NAME

Name of the package (e.g. ``Foobar").

VERSION

Version number of the package, in comma-delimited format (e.g. ``1,0,0,0").

Children

The following elements occur in SOFTPKG: ABSTRACT, AUTHOR, IMPLEMENTATION, LICENSE, TITLE.

Name

TITLE -- -- state the title of the Perl Package

TITLE

Synopsis

<i>Mixed Content Model</i>
<pre>TITLE ::= (#PCDATA)</pre>
<i>Attributes</i>
<i>None</i>

Description

Used to state the title of the Perl Package. Only one instance should be present.

Parents

These elements contain TITLE: SOFTPKG.

Name

UNINSTALL -- -- provide either a reference to an uninstallation script

UNINSTALL

Synopsis

<i>Mixed Content Model</i>		
UNINSTALL ::= (#PCDATA)		
<i>Attributes</i>		
<i>Name</i>	<i>Type</i>	<i>Default</i>
HREF	CDATA	#IMPLIED
EXEC	CDATA	#IMPLIED

Description

Used to provide either a reference to an uninstallation script or a raw Perl script which can be used to uninstall the Perl Package at a later point. Only one instance should be present.

HREF

Reference to an external script which should be retrieved and run as part of the removal process. Both filenames and URLs should be considered valid.

EXEC

Name of interpreter/shell used to execute the uninstallation script. If the value of EXEC is `PPM_PERL', the copy of Perl that is executing PPM itself (\$^X) is used to execute the install script.

Parents

These elements contain UNINSTALL: IMPLEMENTATION.

Examples

Name

Example sample.ppd --

Example sample.ppd

Example sample.ppd

```
<?xml version="1.0"?>
<!DOCTYPE SOFTPKG SYSTEM "ppd.dtd">
<!-- The following is a sample PPD file describing the Math-MatrixBool module.
      Note that this may not be a current/proper description of this module
      and is for sample purposes only.
-->
<SOFTPKG NAME="Math-MatrixBool" VERSION="4,2,0,0">
  <TITLE>Math-MatrixBool</TITLE>
  <ABSTRACT>Easy manipulation of matrices of booleans (Boolean Algebra)</ABS
  <AUTHOR>Steffen Beyer (sb@sdm.de)</AUTHOR>
  <LICENSE HREF="http://www.ActiveState.com/packages/Math-MatrixBool/license
  <IMPLEMENTATION>
    <OS VALUE="WinNT" />
    <OS VALUE="Win95" />
    <PROCESSOR VALUE="x86" />
    <CODEBASE HREF="http://www.ActiveState.com/packages/Math-MatrixBool/Ma
    <DEPENDENCY NAME="Bit-Vector" />
    <INSTALL>
    </INSTALL>
    <UNINSTALL>
    </UNINSTALL>
  </IMPLEMENTATION>

  <IMPLEMENTATION>
    <DEPENDENCY NAME="Bit-Vector" />
    <CODEBASE HREF="&CPAN;/CPAN/modules/by-module/Math/Math-MatrixBool
    <INSTALL>
      system("make"); ;;
      system("make test"); ;;
      system("make install"); ;;
    </INSTALL>
  </IMPLEMENTATION>
</SOFTPKG>
```